

WISI VS 80 A

Multiband amplifier, split band



Description

At a glance:

- Screening class A
- F-socket, 75Ohm

Technical data

Downstream

Inputs	4 pcs.
Frequency range input 1	47...108 MHz
Frequency range input 2	174...230 MHz
Frequency range input 3	470...862 MHz
Frequency range input 4	470...862 MHz
Gain input 1	38 dB (input level regulator 0-18 dB)
Gain input 2	37 dB (input level regulator 0-18 dB)
Gain input 3	42 dB (input level regulator 0-18 dB)
Gain input 4	42 dB (input level regulator 0-18 dB)
Output level 1	119 dB μ V (EN50083-5)
Output test point	-20 dB

Connectors

F-socket	6 pcs.
----------	--------

General data

Operating voltage AC	230 V
Power consumption	3.5 W
Screening factor (EMC)	dB Class A, EN 50083-2
Operating temperature range	-20...+55 °C

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	166 x 143 x 50 mm
	dm ³
Gross weight sales unit	0.860 kg
Shipping unit	10 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	1.2 dm ³
Gross weight shipping unit	0.86 kg
	cm
	N
EAN	4010056170189
Article number	17018
Customs tariff number	8543703000