

WISI GT35

Tangram HD/SD Encoder with HDMI



Description

The TANGRAM Encoder GT35 is a professional and high density HD/SD audio & video encoding device which adds the feature of MPEG-4 and MPEG-2 encoding to the TANGRAM product line. With the same form factor as the TANGRAM modules, the GT35 Encoder can be used in any TANGRAM base unit. GT35 allows you to add services available in HDMI format to your digital network. Per module are 4 HDMI inputs available, which enables 24 HMDI inputs in 1 RU.

Scope of delivery

- 1x GT35 Modul
- 1x Quick Guide

At a glance:

- HD/SD MPEG-4 (AVC, H.264) and HD/SD MPEG-2 video encoding
- Up to 4 HDMI inputs per module
- Professional multiplexer integrated
- SPTS and MPTS streaming (CBR or VBR)
- Supports PSI/SI processing
- Integrated into the TANGRAM Systemmanagement
- Control and management via web-UI

Technical data	
HDMI-Input	
HDMI number of ports	4 pcs. (HDMI)
Input format HDMI	1080p25/30, 1080i50/60/59.94, 720p50/60/59.94, 576p50, 480p60/59.94, 576i50, 480i60/59.94
Input format Audio	PCM (Pulse code modulation)
Compliance	HDMI 1.4a (no scaling)
HDCP Support	No
Video Encoding	
Encoding capacity	4x HD/SD MPEG-2/MPEG-4
Video system	MPEG-2 HD/SD and MPEG-4 HD/SD (H.264/AVC)
Picture size	1080p25/30, 1080i50/60/59.94, 720p50/60/59.94, 576p50, 480p60/59.94, 576i50, 480i60/59.94
Profile MPEG-4	Baseline, Main, High
Bit rate	MPEG-2 10-19Mbps, MPEG-4 6-13Mbps @ 1080p25/30, 1080i50/60/59.94, 720p50/60/59.94; MPEG-2 4-12Mbps, MPEG-4 2-6Mbps @ 576p50, 480p60/59.94; MPEG-2 2-8Mbps, MPEG-4 1-4Mbps @ 576i50, 480i60/59.94
Chroma sample	00-00-0000 04:02:00
Aspect Ratio Conversion	16:9 for HD; 4:3 for SD
Subtitle DVB Support	No
Subtitle OP47 Support	No
Picture size conversion	Downscaling yes, Upscaling no
Frame rate conversion	No
Test pattern	No
Audio Encoding	
Audio-system	ISO 11173-3 (MPEG-1 L2), MPEG-2 AAC (LC)
Number of audio channels	1 per video input @ 4x HD/SD MPEG-2/MPEG-4; 2 per video input @ 2x HD/SD MPEG-2/MPEG-4
Sampling frequency	44.1, 48 kHz
Bit rate	64...288 Kbps (max. MPEG1 L2/AAC)
Audio modes	Stereo, AC-3 pass through
Sampling rate conversion	No
Streaming-In-/Output	
IP-Inputs	
IP-Outputs	
IP-Compliance	ISO/IEC 13818
IP-Input bitrate	Max. 425 Mbit/s per IPTS, Max. 850 Mbit/s total
IP-Output bitrate	Max. 425 Mbit/s per IPTS, Max. 850 Mbit/s total
IP-Input protocol	UDP/RTP/RTP+FEC Unicast and Multicast, IGMP v2 and v3
IP-Output protocol	UDP/RTP/RTP+FEC Unicast and Multicast, IGMP v2 and v3
IP-TS-Input format	SPTS CBR/VBR, MPTS CBR

Technical data	
IP-TS-Output format	SPTS CBR/VBR, MPTS CBR
IP-FEC Inputs	0 or 32 pc. (with GTSTREC Software Option)
IP-FEC Outputs	4 or 32 pc. (with GTSTREC Software Option)
IP-FEC compliance	SMPTE 2022-1, SMPTE 2022-2
IP-Packet format	MPEG over UDP/IP and RTP/IP
IP-Packet size	188 Byte
IP-PCR restamping	Yes
Processing	
Service remultiplexing	
PID filtering and remapping	Yes
PCR correction and de-jitter	Yes
Advanced PSI/SI regeneration	Yes
NIT generation	No
Compliance	ETSI EN 300 468
Processing bitrate	Max. 1200 Mbps total
Number of PIDs	Max. 2000 PIDs total
Connectors	
HDMI input	4 pcs. (for type A connector)
GigE/Control/Power supply (Backplane)	CompactPCI Type C (SGMII)
General data	
Power consumption	max. 18 W
Operating temperature range	-5°C...+45°C, 23°F...113°F, (ETSI EN 300 019-1-3 Class 3.1)
Max. humidity, non condensing	95 %
Electro Magnetic Compatibility (EMC)	DIN EN 55022:2008-05
Hardware revision	1000
Software version	3
Packaging data	
Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	100 x 20 x 250 mm
Packaging volume sales unit	0,5 dm ³
Gross weight sales unit	0.18 kg
Shipping unit	1 pcs.
Dimensions (WxHxD) shipping unit	170 x 75 x 340 mm
Packaging volume shipping package	4,3 dm ³
Gross weight shipping unit	0,340 kg
EAN	4010056764869
Article number	76486
Customs tariff number	85176200