

# WISI DY 0916

PROSWITCH multiswitch 9 in 16, cascade & Stand alone, TERR. pas-  
sive



## Description

The DY 0916 is a cascadable multiswitch with nine inputs for the distribution of two satellites and terrestrial signals. With the separately power supply DY 70 that powers the LNB, the multiswitch is useable as a stand alone device. The polarisations are available at nine cascade outputs for the installation of further multiswitches. Commercially available DVB-S/S2 set-top-boxes or TVs with an integrated receiver can be used at the 16 subscriber outputs. Inserted terrestrial signals like DVB-T/T2, DAB or FM are available at each subscriber output as well. The stand-by functionality minimizes power consumption by activating the multiswitch only in case the connected STB is turned on.

## At a glance:

- Cascadable multiswitch for the distribution of 8 satellite polarisations and terrestrial signals
- Useable as a stand alone device (DY 70 power supply required)
- Stand-by function with connected power supply, optional permanent operation
- Passive terrestrial path to feed in multimedia content or signals from a cable TV operator
- Integrated SAT amplifier for low insertion loss
- Pre-emphasis to compensate the cable loss at high frequencies
- High screening efficiency according to Class A
- Stackable chassis for space-saving installation of various devices
- Colour-coded inputs and outputs
- Compatible with MagentaTV Sat, DIVEO and freenet TV

## Technical data

<b>SAT-IF trunk</b>	
Inputs SAT	8 pcs.
Outputs SAT	8 pcs.
Frequency range SAT	950...2150 MHz
Through loss SAT	1,6...4,5 dB
Decoupling SAT -SAT	40 dB typ.
Return loss SAT	>10 dB

## Terrestrial trunk

Inputs TERR	1 pcs.
Outputs TERR	1 pcs.
Frequency range TERR	5...862 MHz
Through loss TERR	3,5...4,2 dB ( $\pm 1$ dB)
Isolation TERR - SAT	40 dB typ.
Return loss TERR	>15 dB

## Subscriber outputs

Outputs	16 pcs.
Frequency range	5...2150 MHz
TERR type	Passive
Insertion loss SAT	3...-2,2 dB
Insertion TERR	24 dB ( $\pm 3$ dB)
Max. output level subscriber SAT	90 dB $\mu$ V
Max. output level subscriber TERR	81 dB $\mu$ V (passive)
Return loss subscriber SAT	>10 dB
Return loss subscriber TERR	>14 dB
Control signal	14/18 V, 0/22 kHz, DiSEqC 2.0
Current consumption from receiver	50 mA

## Connectors

F-female	36 pcs.
DC supply voltage	F-female
Colour-coding	VL = black; HL = green; VH = red; HH = yellow

## General data

Power indicator	LED
Operating voltage	10...19 V DC
Power consumption max.	<0,2 W
Screening factor	Class A, according to EN 50083-2
Impedance	75 $\Omega$
Operating temperature range	-20...+50 °C
Cascadable with	DY 0908
Weight	0,7 kg
Dimensions (width x height x depth)	206 x 206 x 32 mm

## Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	275 x 265 x 40 mm
Packaging volume sales unit	3,2 dm <sup>3</sup>
Gross weight sales unit	0.86 kg
Shipping unit	1 pcs.
Dimensions (WxHxD) shipping unit	270 x 170 x 70 mm

## Packaging data

Packaging volume shipping package	3,2 dm <sup>3</sup>
Gross weight shipping unit	0,68 kg
EAN	4010056736248
Article number	73624
Customs tariff number	85437090