

WISI VX 67 B

In-house amplifier



Description

Broadband in-house amplifier for use in coaxial networks with direct connection for up to 4 antenna outlets.

At a glance:

- Adjustable level and equalizer
- F-connectors
- Wall mounting
- Metal housing

Technical data

Downstream	
Inputs	1 pcs.
Frequency range downstream	85...1006 MHz
Gain downstream	6 dB
Output level 1	≥87 dB μ V (CENELEC 42 channels, flat, at CSO/CTB >60 dB)
Upstream	
Frequency range upstream	5...65 MHz
Gain upstream	1 dB
Noise figure upstream	≤18 dB
Output level 4	116 dB μ V (DIN. IMA2/3 >50 dB)
Connectors	
F-female	5 pcs.
General data	
Operating voltage AC	230 V (\pm 10 %)
Power consumption	3 W
Screening factor	Class A, EN 50083-2
Dimensions (width x height x depth)	165x105x45 mm
Operating temperature range	-25...+75 °C
Protection class	IP20

Packaging data

Sales unit	1 pcs.
Dimensions (WxHxD) sales unit	166 x 150 x 50 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.87 kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	1.2 dm ³
Gross weight shipping unit	0.87 kg
EAN	4010056715960
Article number	71596
Customs tariff number	85437030