

WISI DM 21 C

One-way tap, 8 dB



Description

The DM 21 C is a simple splitter for cable TV. Its insertion loss is 2 dB and its tap loss is 8 dB. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets. The DM 21 C is also return path compatible and suitable for internal installation.

At a glance:

- Frequency range 5...1000 MHz
- Screening factor according to Class A
- High port isolation and return loss

Technical data

Frequency range	5...1006 MHz
Through loss	1,5...2,0 dB
TAP loss	8 dB
Directional attenuation	30/25 dB (5...470/470...1000 MHz)
Return loss	18...22 dB

Connectors

F-female	3 pcs. (1x input, 1x run through, 1x branch)
----------	--

General data

Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	No
Dimensions (width x height x depth)	55 x 50 x 28 mm

Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	370 x 320 x 200 mm
Packaging volume sales unit	dm ³
Gross weight sales unit	0.046 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	0.24 dm ³
Gross weight shipping unit	0.046 kg
EAN	4010056702991
Article number	70299
Customs tariff number	85437090