

# WISI DM 34 C

Two-way tap, 16 dB



## Description

The DM 34 C is a double splitter for cable TV. Its insertion loss is 1.2 dB and its tap loss is 16 dB. High shielding properties (class A) guarantee an interference-free transmission of the signals in the input and distribution systems. A fast and safe connection is ensured through F-sockets. The splitter is also return path compatible and suitable for internal installation.

## At a glance:

- Frequency range 5...1000 MHz
- Screening factor according to Class A
- High port isolation and return loss

## Technical data

Frequency range	5...1006 MHz
Through loss	0,8...1,2 dB
TAP loss	16 dB
Directional attenuation	≥35/≥28 dB (5...470/470...1000 MHz)
Isolation	≥34 dB
Return loss	18...22 dB
<b>Connectors</b>	
F-female	4 pcs. (1x input, 1x run through, 2x branch)
<b>General data</b>	
Screening factor	>85 dB (class A)
DC Bypass IN/OUT 1A/30V	No
Dimensions (width x height x depth)	78 x 50 x 27 mm

Sales unit	10 pcs.
Dimensions (WxHxD) sales unit	370 x 320 x 170 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	0.062 kg
Shipping unit	100 pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	0.062 kg
EAN	4010056703059
Article number	70305
Customs tariff number	85437090