

# WISI VX 1014

In-house amplifier



## Description

### At a glance:

- Zinc pressure cast housing - home line
- Return path amplifier and diplex-filter modular
- ICS option modular
- Damping adjustment and equaliser adjustment interruption-free with Q-step switcher

## Technical data

### Downstream

with US-module VX 101-0650

Frequency range	85...1006 MHz (without US-module)
Return loss	≥ 18 dB (-1,5 dB/Oct.)
Gain	15 dB (±0,5 dB)
Frequency response	typ. ± 0,5 dB (max. ± 0,8 dB)
cable simulator downstream	0/5/10 dB (Jumper)
Attenuator downstream	0...15 dB (Q-Step 1dB step size)
Equalizer downstream	0...22,5 dB (Q-Step 1.5 dB step size)
output level CC 101 channels flat	CTB / 66 dB ≥ 97 dBμV, CSO / 66 dB ≥ 95 dBμV
Noise figure	typ. 6 dB (max. 8 dB)
Test point downstream output	-20 dB (directional coupler)

### Upstream

with US-module VX 101-0650

Frequency range	5...65 MHz
Return loss	≥ 18 dB ≥ 40 MHz 18 dB -1,5dB/Okt.
Gain	10 dB (± 0,75 dB)
Frequency response	typ. ± 0,5 dB (max. ± 0,8 dB)
Attenuator upstream output	0...15 dB (Q-Step 1dB step size)
Noise figure	< 6 dB
output level DIN - IMA 2	typ. 108 min. 106 dBμV
output level DIN - IMA 3	typ. 114 min 112 dBμV

### ICS Option

Ingress Control Switch (ICS)	0/6/40 dB
------------------------------	-----------

### General data

RF connectors	F
Impedance	75 Ω
Supply voltage	230 V AC
Power consumption max.	< 6 W
Ambient temperature	-20...+55 °C
Protection class	IP 20
EMC	EN50083-2
Surge protection RF Ports	2 kV (1,2/50 μs pulse EN61000-4-5)
Dimensions (width x height x depth)	163 x 90 x 47 mm

## Packaging data

Sales unit	pcs.
Dimensions (WxHxD) sales unit	163 x 90 x 47 mm
Packaging volume sales unit	dm <sup>3</sup>
Gross weight sales unit	kg
Shipping unit	pcs.
Dimensions (WxHxD) shipping unit	mm
Packaging volume shipping package	dm <sup>3</sup>
Gross weight shipping unit	kg
EAN	4010056732950
Article number	73295

## Packaging data

Customs tariff number	85437030
-----------------------	----------